Via Germania, 34 - 35127 Padova
Tel. +39049.8705.359-408-355
Fax +39049.8706287
email info@seneca.it

ANALOGUE SIGNALS PROCESSORS

S113S - SINGLE ALARM THRESHOLD FOR ANALOGUE SIGNALS

Single alarm threshold for control of analogue signals.

Widely used as alarm unit in control of temperature, pressure, flow rate, level etc.

The analogue input can be programmed via dip switches for all the standard signals used industrially:
- current 0 - 20 mA and 4 - 20 mA
- voltage 0 - 5 Vdc, 1 - 5 Vdc, 0 - 10 Vdc and 2 - 10 Vdc.



The alarm threshold can be adjusted from 1 % to 100 % of the signal to be controlled via multi-turn trimmers with checking of calibration value by means of an ordinary tester.

The hysteresis at reset is fixed and equal to 2 % of the cut-in value. The cut-in delay can be adjusted by means of trimmers from 0 to 45 seconds.

The output is of the relay type with 1 SPDT changeover with capacity 5 A 250 Vac (resistive load).

Two signaling LED on the front panel indicates power on and threshold exceeded.

The self-extinguishing Noryl case is the width of 3 DIN modules and is designed to fit on a 35 mm mounting rail (DIN 46277).

TECHNICAL DATA

- Power supply : 115 / 230 Vac +/- 10% 50 / 60 Hz
- Power consumption : 1,5 VA
- Current input : selectable via DIP-switches between 0-20 and 4-20 mA
- Voltage input : selectable via DIP-switches between 0-5, 1-5, 0-10 and 2-10 Vdc
- Input impedance :
  - 250 ohm for current input
  - 1 Mohm for voltage input
- Output : 1 relay with 1 SPDT changeover 5 A 250 Vca (resistive load)
- Threshold adjustment : from 1 to 100% of range
- Delay adjustment : from 0 to 45 seconds
- Operating temp. : 0 / + 60 °C
- Humidity : 90 % a 40 °C (non-condensing)
- Dimensions (b x h x d) : 52,5 x 95 x 72 mm
- Weight : approx. 200 g.

ORDERING CODES

Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Code	Power supply
S113S-1-ST	115 - 230 Vac
Z113S	24 Vdc-ac

For more info please refer to the operating manual

Characteristics can be subject to change without notice